
Product Category
Product Line
Part Description

670-0
O-SEAL® Check Valves (600 Series)
1/8" Globe Check Valve with Welded Ends



## **DIMENSIONS**

| Port Dia.     | 0.22  |
|---------------|-------|
| A             | 3.250 |
| В             | 1.50  |
| D             | 0.380 |
| F (Pipe Size) | 0.420 |
| F (Tube Size) | 0.252 |

## **GENERAL**

| Pressure Rating     | 6000 PSI                                      |
|---------------------|---|
| Temperature Range   | -15°F to 275°F (-26°C to 135°C)               |
| Standard Soft Goods | [-C] Viton® O-Rings                           |
| Cartridge Type      | Check   |
| Connection Type     | Socketweld                                    |
| Connection Size     | 1/8"  |
| Body Material       | 316/L Stainless Steel, ASTM A276, UNS S31603  |
| Bonnet Material     | Nickel Aluminum Bronze, ASTM B150, UNS C63200 |

https://www.cpvmfg.com 484.731.4010



## **OPTIONS**

| Port & Vent Options | [-PA] Port Above Seat (1/8" NPT), [-PB] Port Below Seat (1/8" NPT), '[-VA] Vent Above Seat (3/8"-24 SAE), [-VB] Vent Below Seat (3/8"-24 SAE), |
|---------------------|--|
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings                                      |

https://www.cpvmfg.com 484.731.4010