04/29/2025 4:26 AM


670-5



MANUFACTURING

Product Category
Product Line
Part Description

670-5
O-SEAL® Check Valves (600 Series)
1.00" Globe Check Valve with Welded Ends



DIMENSIONS

| Port Dia. | 0.81 |
|---------------|-------|
| A | 6.750 |
| В | 3.25 |
| D | 0.630 |
| F (Pipe Size) | 1.330 |
| F (Tube Size) | 1.252 |

GENERAL

| Pressure Rating | 6000 PSI |
|---------------------|---|
| Temperature Range | -15°F to 275°F (-26°C to 135°C) |
| Standard Soft Goods | [-C] Viton® O-Rings |
| Cartridge Type | Check |
| Connection Type | Socketweld |
| Connection Size | 1.00" |
| Body Material | 316/L Stainless Steel, ASTM A276, UNS S31603 |
| Bonnet Material | Nickel Aluminum Bronze, ASTM B150, UNS C63200 |

https://www.cpvmfg.com 484.731.4010



OPTIONS

| Port & Vent Options | [-PA] Port Above Seat (1/4" NPT), [-PB] Port Below Seat (1/4" NPT), '[-VA] Vent Above Seat (1/2"-13 SAE), [-VB] Vent Below Seat (1/2"-13 SAE), |
|---------------------|--|
| Optional Soft Goods | [-B] Polyurethane® Packing and Buna-N O-Rings, [-C] Viton® Packing & O-Rings, [-D] EPDM Packing & O-Rings |

https://www.cpvmfg.com 484.731.4010