

DATA SHEET


H810-04-M

H810-04-M 12/26/2024 7:49 PM

Socketweld/braze Tube Tee Assembly

Product Category

Part Description



DIMENSIONS

A	0.250
A'	0.250
A"	0.250
C-HEX	0.63
D	0.190
D'	0.190
D"	0.190
F	1.19
G	1.19

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.



GENERAL

Pressure Rating	6000 PSI
Tailpiece Material	Monel®, ASTM B164, UNS N04405
Threadpiece Material	Monel®, ASTM B564, UNS N04400
O-Ring Material	Viton® Fluorocarbon Type 1, Class 2 (90 durometer)
Connection 1 Type	Female Tube Socket
Connection 1 Size	1/40 Tube O.D. (-04)
Connection 2 Type	Female Tube Socket
Connection 2 Size	1/40 Tube O.D. (-04)
Connection 3 Type	Female Tube Socket
Connection 3 Size	1/40 Tube O.D. (-04)

https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.