#### DATA SHEET

H823-06-10-SS316L 12/26/2024 8:30 PM




American Engineering Trusted Wordwide

### **Product Category**

**Part Description** 

H823-06-10-SS316L

Tube to Male Straight Thread Elbow Assembly



# DIMENSIONS

| Α        | 0.380         |
|----------|---------------|
| B-THREAD | .875" - 14UNF |
| C-HEX    | 1.13          |
| D        | 0.250         |
| E        | 1.94          |
| F        | 1.69          |

# **GENERAL**

| Pressure Rating   | 6000 PSI   |
|-------------------|--|
| Assembly Material | 316/L Stainless Steel, ASTM A276, UNS S31600/03    |
| O-Ring Material   | Viton® Fluorocarbon Type 1, Class 2 (90 durometer) |
| Connection 1 Type | Female Tube Socket                                 |
| Connection 1 Size | 3/8" Tube O.D. (-06)                               |
| Connection 2 Type | Male Straight Thread                               |
| Connection 2 Size | .875" - 14UNF (-10)                                |

#### https://www.cpvmfg.com 484.731.4010

The complete catalog contents must be reviewed to ensure that the system designer and user make a safe product selection. When selecting products, the totabystem design must be considered to ensure safe, trouble-free performance. Function, material compatibility, adequate ratings, proper installation, operation, and maintenance are the responsibilities of the system designer and user. Caution: Do not mix or interchange valve components with those of other manufacturers.